

THROUGH HOLE CLOCK OSCILLATOR SPECIFICATION

General Information


Product Type: 5.0V OSC(14PIN DIP)
Packagte Type: **EZOF5**
Part No.: Freq.-Series-EZT & datecode

Electrical Specifications

Frequency: 20KHz~160.000MHz
Calibration Frequency Tolerance: $\pm 20\text{ppm} \sim \pm 50\text{ppm}$ @ 25°C
Frequency Stability over Temp.: $\pm 20\text{ppm}$, $\pm 25\text{ppm}$, $\pm 50\text{ppm}$
Operating Temperature: 0~+70°C, -40~+85°C(option)
Storage Temperature: -55°C ~ +125°C
Supply Voltage(Vdd): +5.0Vdc $\pm 0.5\text{Vdc}$
Supply Current: 20~30mA max@20kHz to 34.999MHz
40~60mA max@35.0~160.000MHz
Symmetry (Duty Cycle): 40/60% Std., 45/55% Available
Output "O" Level: 0.4Vdc max (TTL), 0.5 Vdc max (HCMOS)
Output "1" Level: 2.4 Vdc min (TTL), 4.5Vdc min (HCMOS)
Rise & Fall Time: 10nS max < 5nS typical
Output Load: 15pF or 10 LS TTL Standard
Srart time: 10mS Max < 5mS typical
Aging: $\pm 5.0\text{ppm}$ per year

Package Dimensions

L x W x H
20.8 x 13.2 x 7.6mm



Marking

Line 1 Frequency
Line 2 Series
Line 3 EZT & datecode

74.250
EZOF5
EZT 401

Pin	Function
1	NC, Tri-State
2	GND
3	OUTPUT
4	Vdd

EZTeck

Room#502, V-Charmant Building, 1601-1
Seocho-Dong, Seocho-Gu, Seoul,Korea
Phone : +82 2 582 1982 Fax : +82 2 582 1984

DWG. No.: EZOF5-04

REV.:

DATE:

BY: Richard Lee

PAGE: 1 of 1

APPROVAL: