

THROUGH HOLE CLOCK OSCILLATOR SPECIFICATION

General Information



Product Type: 3.3V OSC(8PIN DIP)
 Package Type: **EZO3**
 Part No.: Freq.-Series-EZT & datecode

Electrical Specifications

Frequency: 20kHz to 200.000MHz
 Calibration Frequency Tolerance: $\pm 20\text{ppm} \sim \pm 50\text{ppm}$ @ 25°C
 Frequency Stability over Temp.: $\pm 20\text{ppm}$, $\pm 25\text{ppm}$, $\pm 50\text{ppm}$
 Operating Temperature: 0~+70°C, -40~+85°C(option)
 Storage Temperature: -55°C ~ +125°C
 Supply Voltage(Vdd): +3.3Vdc $\pm 0.3\text{Vdc}$
 Supply Current: 20~30mA max@20kHz to 34.999MHz
 40~60mA max@35.0~200.000MHz
 Symmetry (Duty Cycle): 40/60% Std., 45/55% Available
 Output "O" Level: 0.4Vdc max (TTL), 0.4 Vdc max (HCMOS)
 Output "1" Level: 2.4 Vdc min (TTL), 2.7 Vdc min (HCMOS)
 Rise & Fall Time: 10nS max < 5nS typical
 Output Load: 15pF or 10 LS TTL Standard
 Start time: 10mS Max < 5mS typical
 Aging: $\pm 5.0\text{ppm}$ per year

Package Dimensions

L x W x H
 13.20 x 13.20 x 5.08mm



Marking

Line 1 Frequency
 Line 2 Series
 Line 3 EZT & datecode

18.000
EZO3
EZT 401

Pin	Function
1	NC, Tri-State
2	GND
3	OUTPUT
4	Vdd

EZTeck	
Room#502, V-Charmant Building, 1601-1 Seocho-Dong, Seocho-Gu, Seoul, Korea Phone : +82 2 582 1982 Fax : +82 2 582 1984	
DWG. No.: EZO3-04	REV.:
DATE:	BY: Richard Lee
PAGE: 1 of 1	APPROVAL: